

Fuel Oil

| Property | Unit | Test | Value |
|---------------------------|----------------------|-------------|--------|
| | | ASTM D 4052 | 0.9798 |
| API | | ASTM D 1298 | 12.92 |
| SULPHUR CONTENT (Total) | wt% | ASTM D 4294 | 2.85 |
| BASE SEDIMENT & WATER | vol% | ASTM D 1796 | 0.05 |
| WATER CONTENT | vol% | ASTM D 4006 | <0.05 |
| SALT CONTENT | P.T.B | ASTM D 3230 | 10 |
| F | | ASTM D 93 | 164 |
| " | mm ² /Sec | ASTM D 445 | 907 |
| " | mm ² /Sec | ASTM D 445 | 376 |
| POUR POINT | | ASTM D 5853 | 3 |
| ASH CONTENT | Wt.% | ASTM D 482 | 0.03 |
| ASPHALTENES | wt% | IP 143 | 5.4 |
| Wt.% | | | |
| WAX CONTENT | wt% | BP 237 | 7.5 |
| DROP MELTING POINT OF WAX | | IP 133 | 72 |
| CARBON RESIDUE CONRADSON | wt% | ASTM D 189 | 13.4 |
| ACIDITY , TOTAL | mgKOH/gr | UOP 565 | 0.08 |
| CALORIFIC VALUE | Kcal/Kg | CALCULATED | 10141 |
| NICKEL CONTENT | PPm | ASTM D 5863 | 39 |
| PPm | PPm | ASTM D 5863 | 137 |
| PPm | PPm | ASTM D 5863 | <1 |
| PPm | PPm | ASTM D 5863 | <1 |
| PPm | PPm | ASTM D 5863 | 13 |

